

TRIMBLE M1 DR TOTAL STATION

KEY FEATURES

2" and 5" angle accuracies

Prism and DR measurements

Fast, accurate EDM provides fast, reliable measurements

Long life Li-ion Battery

Easy-to-use keypad

Rugged and lightweight system design



DEPENDABILITY FOR YOUR SURVEY CREWS

The Trimble® M1 DR Total Station is a versatile, easy to use, conventional surveying instrument that provides Trimble dependability at an affordable price.

You work in demanding environments and require reliable and efficient equipment that will work as hard as you do. The Trimble M1 DR Total Station is a compact, lightweight, and rugged total station tough enough for everyday use.

PROVEN RANGE, ACCURACY, AND QUALITY FROM TRIMBLE

Available in 2" dual face or 5" single face models, the Trimble M1 meets your specific accuracy requirements. Both Trimble M1 models provide 3000 m range to a single prism and up to 400 m DR (Direct Reflex) range to non-reflective surfaces.

The EDM in the M1 provides high precision measurements to both reflective and non-reflective surfaces and includes improved measurement speed for fast and accurate results in typical surveying environments.

Equipped with legendary Nikon optics, the Trimble M1 provides proven clarity, quality and precision. The result is efficient operation and comfort throughout the workday.

SIMPLE, INTUITIVE ONBOARD SOFTWARE

The M1 includes easy-to-use dual or single face keypads to operate the instrument. The intuitive and field-proven interface and onboard data collection software is fast to learn so that you can have your crews up and running quickly. The backlit display is easy to see in low light environments. Two user-programmable measure keys allow you to separately configure measurement parameters, eliminating time switching between measurement modes.

BLUETOOTH CONNECTIVITY TO EXTERNAL CONTROLLER

Each M1 instrument comes standard with an integrated wireless Bluetooth® connection. Through this connection, users can control the instrument using the power of Trimble Access™ field software on an external controller such as the Trimble TSC3. Measurements are stored directly in the Trimble Access job on the external controller. Use the Trimble M1 seamlessly right along with other Trimble solutions on the job site.

RUGGED, LIGHTWEIGHT AND FEATURE PACKED FOR LONG DAYS IN THE FIELD

The Trimble M1 is small, lightweight, and durable, allowing for easy transport in and around the job site. Each system comes with two rechargeable long life Li-ion batteries and a dual battery charger providing enough power for even the longest of field days.

A visible coaxial red laser pointer is included for fast and easy aiming along with internal optical plummet for easy known point setups.

Packed with all these features and more, the Trimble M1 DR Total station is ready to become a trusted piece of your everyday surveying equipment set.

TRIMBLE M1 TOTAL STATION

DISTANCE MEASUREMENT

Range with specified prisms
 Good conditions¹ (No haze, visibility over 40 km (25 miles))
 With reflector sheet 5 cm x 5 cm (2 in x 2 in) 1.5 m to 200 m
 (4.9 ft to 656 ft)
 With single prism 6.25 cm (2.5 in) 3,000 m (9,842 ft)
 Reflectorless mode

	Good	Normal	Difficult
KGC (18%) ¹	250 m (820 ft)	200 m (656 ft)	150 m (492 ft)
KGC (90%) ¹	400 m (1312 ft)	350 m (1148 ft)	250 m (820 ft)

Accuracy ISO 17123-4 (Precise mode)
 Prism² ±(2+2 ppm x D) mm
 Reflectorless/Reflector sheet³ ±(3+3 ppm x D) mm
 Measuring interval⁴
 Prism mode
 Precise mode 1.8 sec.
 Normal mode 0.8 sec.
 Reflectorless mode
 Precise mode 1.8 sec.
 Normal mode 1.0 sec.
 Least count
 Precise mode 1 mm (0.002 ft)
 Normal mode 10 mm (0.02 ft)

ANGLE MEASUREMENT

ISO 17123-3 accuracy (horizontal and vertical) 2"/0.6 mgon
 5"/1.5 mgon
 Reading system Photoelectric detection by incremental encoder
 Circle diameter 88 mm (3.46 in)
 Horizontal angle 2: Diametrical
 5": Single
 Vertical angle Single
 Minimum increment (Degree, Gon, MIL6400) Degree: 1/5/10"
 Gon: 0.2/1/2 mgon
 MIL6400: 0.005/0.02/0.05 mil

TELESCOPE

Tube length 125 mm (4.9 in)
 Image Erect
 Magnification 30x (18x/36x with optional eyepieces)
 Effective diameter of objective 45 mm (1.8 in)
 EDM diameter 50 mm (1.97 in)
 Field of view 1°20'
 Resolving power 3"
 Minimum focusing distance 1.5 m (4.9 ft)
 Laser Pointer Coaxial Red Light

1 Kodak Gray Card, Catalog number E1527795.
 2 ±(2+3 ppm x D) mm -20 °C to -10 °C, +40 °C to +50 °C (-4 °F to +14 °F, +104 °F to +122 °F)
 1.5 m to 5 m ± (5 + 3 ppm x D) mm.
 3 1.5 m to 5 m ± (10 + 3 ppm x D) mm.
 4 Measuring time may vary depending on measuring distance and conditions. Specification based on average of multiple measurements.
 5 Battery life specification at 25 °C (77 °F). Operation time may be shorter if battery is not new. Operation time may be shorter in low temperatures.

© 2013, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Access is a trademark of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. PN 022516-001A (12/13)

TILT SENSOR

Type Single-axis
 Method Liquid-electric detection
 Compensation range ±3'
 Setting accuracy 1"

COMMUNICATIONS

Communication ports 1 x serial (RS-232C)
 Wireless communications Integrated Bluetooth
 Raw and coordinate data formats Nikon, SDR2x, SDR33

POWER

Clip-on Li-ion battery
 Output voltage 3.8 V DC
 Operating time⁵ approx. 11 hours (distance/ angle measurement every 30 seconds)
 approx. 22 hours (continuous angle measurement)
 Charging time, full charge 4 hours

GENERAL SPECIFICATIONS

Level vials
 Sensitivity of Plate level vial 30"/2 mm
 Sensitivity of Circular level vial 10"/2 mm
 Optical plummet
 Image Erect
 Magnification 3x
 Field of view 5°
 Focusing range 0.5 m (1.6 ft) to ∞
 Display 2": Both sides, backlit, graphic LCD (128 x 64 pixel);
 5": Single side, backlit, graphic LCD (128x64 pixel);
 Optional 2nd face display available for 5" models.
 Point memory 10,000 records
 Dimensions (W x D x H) 168 mm x 173 mm x 355 mm
 (6.6 in x 6.8 in x 13.1 in)
 Weight (approx.)
 Main unit (without battery) 4.9 kg (10.8 lb)
 BC-65 battery 0.1 kg (0.2 lb)
 Carrying case 2.5 kg (5.5 lb)
 Dual charger and AC adaptor 0.6 kg (1.3 lb)

ENVIRONMENTAL

Ambient temperature range -20 °C to +50 °C (-4 °F to +122 °F)
 Atmospheric correction
 Temperature range -40 °C to +60 °C (-40 °F to +140 °F)
 Barometric pressure 400 mmHg to 999 mmHg/533 hPa to
 1,332 hPa/15.8 inHg to 39.3 inHg
 Dust and water protection IP54

CERTIFICATION

Class B Part 15 FCC certification, CE Mark approval.
 Laser safety IEC60825-1:2007
 Reflectorless mode: Class 1
 Laser Pointer : Class 2
 Prism mode: Class 1

Bluetooth type approvals are country specific.
 Specifications subject to change without notice.



TRIMBLE AUTHORIZED DISTRIBUTION PARTNER

NORTH AMERICA

Trimble Navigation Limited
 10368 Westmoor Dr
 Westminster CO 80021
 USA

EUROPE

Trimble Germany GmbH
 Am Prime Parc 11
 65479 Raunheim
 GERMANY

ASIA-PACIFIC

Trimble Navigation
 Singapore Pty Limited
 80 Marine Parade Road
 #22-06, Parkway Parade
 Singapore 449269
 SINGAPORE

